# NSN 5305-01-016-4864

Setscrew - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.428 inches and 0.448 inches

## Fastener Length:

Between 0.428 inches and 0.448 inches

#### **Head Style:**

Headless (setscrew)

#### Hole Diameter:

0.053 inches

#### Point Style:

Half dog

#### Internal Drive Style:

-----

# Hexagon

Thread Diameter:

0.190 inches

# Width Across Flats:

Between 0.094 inches and 0.095 inches

### Hole Quantity:

3

### Hole Type:

Drilled

### Thready Qty Per Inch (tpi):

32

#### Hardness Rating:

45.0 rockwell c and 53.0 rockwell c

#### Hole Configuration Style:

Hexagon longitudinal hole

#### Material:

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

#### Material Specification:

66 federal standard all material responses

#### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Qq-p-416, ty2 cl 2 federal specification single treatment response

# Thread Series Designator:

Unf

# Shelf Life:

N/a

# NSN 5305-01-016-4864

Setscrew - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

