## NSN 5305-01-016-6019

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-016-6019           |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.160 inches  |
| Fastener Length:  |
| 0.440 inches  |
| Head Style:   |
| Pan   |
| Head Diameter:  |
| Between 0.256 inches and 0.270 inches                                   |
| Head Height:  |
| Between 0.087 inches and 0.097 inches                                   |
| First Diameter From Head:   |
| 0.098 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.280 inches  |
| Internal Drive Style:   |
| Cross recess type 1   |
| Thread Diameter:  |
| 0.138 inches  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Min. Tensile Strength (psi):  |
| 730 pounds per square inch  |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Material:   |
| Stainless steel   |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response                 |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |

No

## NSN 5305-01-016-6019

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0