## NSN 5305-01-017-0088



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-017-0088 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.745 inches and 0.847 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.452 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** 82.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-225/6, t4 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No Fiig:

A500d0

## NSN 5305-01-017-0088

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.