## NSN 5305-01-017-7891

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-017-7891 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.670 inches and 0.702 inches **Fastener Length:** Between 0.672 inches and 0.704 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 75000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0

## NSN 5305-01-017-7891

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072 spec.