## NSN 5305-01-017-9659

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-017-9659

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.350 inches and 0.400 inches
Fastener Length:
Between 1.672 inches and 1.702 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.577 inches and 0.635 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches
Material:
Steel comp 4140
Material Specification:
Mil-s-5626, cond 4340 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1155 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
- · · · · · · · · · · · · · · · · · · ·

## NSN 5305-01-017-9659

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.