

View Online at <https://aerobasegroup.com/nsn/5305-01-018-8910>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.201 inches

**Fastener Length:**

Between 0.700 inches and 0.750 inches

**Head Style:**

Undercut universal

**Head Diameter:**

Between 0.218 inches and 0.226 inches

**Head Height:**

Between 0.134 inches and 0.138 inches

**First Diameter From Head:**

Between 0.098 inches and 0.103 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.499 inches and 0.549 inches

**Point Style:**

Cone

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

Between 0.1094 inches and 0.1111 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

155000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0