## NSN 5305-01-019-3722

A003b0

Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-019-3722

| view offilite at https://defobasegroup.com/hsh/osos-01-013-3/22  |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.000 inches   |
| Fastener Length:   |
| Between 1.938 inches and 2.000 inches  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.226 inches and 0.243 inches  |
| Width Between Flats:   |
| Between 0.551 inches and 0.562 inches  |
| Thread Diameter:   |
| 0.375 inches   |
| Thready Qty Per Inch (tpi):  |
| 16   |
| Hardness Rating:   |
| 23.0 rockwell c and 34.0 rockwell c  |
| Material:  |
| Steel  |
| Surface Treatment:   |
| Zinc   |
| Special Test Features:   |
| Special quality control testing  |
| Surface Treatment Specification:   |
| F70b4a, fscm 05606 mfr ref single treatment response   |
| Test Data Document:  |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Unc  |
| Reference Number Differentiating Characteristics:  |
| As differentiated by material which must conform to ships parts control center special quality control provisions                            |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |