

View Online at <https://aerobasegroup.com/nsn/5305-01-019-4305>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.359 inches and 0.391 inches

Fastener Length:

Between 0.922 inches and 0.954 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.433 inches and 0.443 inches

Head Height:

Between 0.234 inches and 0.266 inches

First Diameter From Head:

Between 0.115 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.531 inches and 0.595 inches

Point Style:

Cone

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Product Name:

Thumbscrew

Material:

Steel comp 303

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by packaging which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.