NSN 5305-01-019-5631

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-019-5631 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.334 inches and 0.416 inches **Fastener Length:** Between 1.344 inches and 1.406 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.531 inches and 0.593 inches **Head Height:** Between 0.234 inches and 0.266 inches **Hole Diameter:** 0.063 inches First Diameter From Head: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.990 inches and 1.010 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:**

Surface Treatment Specification:

Passivate

Mil-f-14072, finish e300 military specification single treatment response

NSN 5305-01-019-5631

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072 spec.