NSN 5305-01-019-9659

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-019-9659 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.150 inches and 0.160 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.095 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.247 inches and 0.288 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316l o comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 301 or steel comp 303 or steel comp 301 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 308 or steel comp 309s or steel comp 310s or steel comp 314 or steel comp 323 or steel comp 324 or steel comp 348 or steel comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

NSN 5305-01-019-9659

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0