

View Online at <https://aerobasegroup.com/nsn/5305-01-020-5921>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.245 inches and 0.312 inches

**Fastener Length:**

Between 0.281 inches and 0.312 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.124 inches and 0.140 inches

**Head Height:**

Between 0.055 inches and 0.062 inches

**Hole Diameter:**

0.031 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.086 inches

**Hole Quantity:**

1

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Stainless steel

**Screw Material Specification:**

Ams 5616 federal specification single material response

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924, cl 4 military specification single treatment response

**Head Hole Configuration Style:**

Hexagon flats

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 5s style

**Departure From Cited Document:**

As modified by surface treatment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.