NSN 5305-01-020-5930

Thread Class:

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-020-5930

| 3a |
|--|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.400 inches and 0.450 inches |
| Fastener Length: |
| Between 0.660 inches and 0.690 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.367 inches and 0.375 inches |
| Head Height: |
| Between 0.133 inches and 0.150 inches |
| Locking Feature: |
| Patch threads or pellet threads or strip threads |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Plastic locking feature |
| Material Specification: |
| Ams5737 assn standard single material response fastener |
| Surface Treatment: |
| Passivate fastener |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response fastener |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1184 professional/industrial association standard |
| |

NSN 5305-01-020-5930

Close Tolerance Screw - Page 2 of 2



| _ | | | | | |
|---|-----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | 116 | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0