NSN 5305-01-020-5930

Thread Class:

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-020-5930

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 0.660 inches and 0.690 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.367 inches and 0.375 inches
Head Height:
Between 0.133 inches and 0.150 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Plastic locking feature
Material Specification:
Ams5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:
80205-nas1184 professional/industrial association standard

NSN 5305-01-020-5930

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0