

View Online at <https://aerobasegroup.com/nsn/5305-01-020-6882>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.189 inches and 0.220 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.162 inches and 0.175 inches

First Diameter From Head:

0.200 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.280 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 304l or steel comp 316l or steel comp 302 or steel comp 347 or steel comp 321 or steel comp 317 or steel comp 316 or steel comp 310 or steel comp 309 or steel comp 305 or steel comp 304 or steel comp 301 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 308 or steel comp 309s or steel comp 310s or steel comp 314 or steel comp 323 or steel comp 324 or steel comp 348 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.