## NSN 5305-01-020-9496

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-020-9496 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.308 inches and 0.375 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.124 inches and 0.140 inches **Head Height:** Between 0.053 inches and 0.062 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Steel comp 304 or steel comp 385 **Screw Material Specification:** Qq-s-763 federal specification 1st material response or federal standard 66 federal standard 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-std-171.5.4 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

A500d0

**Demilitarization:** 

## NSN 5305-01-020-9496

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-std-171 spec.