3a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-021-2530



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.169 inches and 0.250 inches Fastener Length: Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.178 inches and 0.183 inches **Head Height:** Between 0.059 inches and 0.069 inches Locking Feature: Patch threads or pellet threads or strip threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Plastic polyamide locking feature **Material Specification:** Mil-f-18240 military specification single material response locking feature Surface Treatment: Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1191 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

NSN 5305-01-021-2530

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.