NSN 5305-01-021-3438

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-021-3438 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** 0.319 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 27.0 rockwell c and 32.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel **Screw Material Specification:** Mil-s-7839 military specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas514 professional/industrial association standard

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-021-3438

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7839 spec.