NSN 5305-01-021-3742

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-021-3742 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.303 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.154 inches and 0.161 inches **Head Height:** Between 0.095 inches and 0.099 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.099 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-021-3742

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0