## NSN 5305-01-021-3749

**Demilitarization:** 

No

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-021-3749 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.514 inches and 0.596 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.213 inches and 0.225 inches **Locking Feature:** Patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Surface Treatment:** Passivate and cadmium and chromate **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response and qq-p-416 type 2, cl 2 federal specification 2nd treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1741 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

## NSN 5305-01-021-3749

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0