Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-022-0147

т	hread Class:	
3		
-	a hread Direction:	
	ight-hand	
	hread Length: .312 inches	
-		
	astener Length: etween 1.124 inches and 1.129 inches	
	lead Style: lat chamfer	
	ead Diameter:	
	etween 0.306 inches and 0.313 inches	
	ead Height:	
	etween 0.103 inches and 0.118 inches	
	irst Diameter From Head:	
	etween 0.131 inches and 0.136 inches	
	istance From Largest Bearing Surface Of Head To End Of First Diameter:	
	etween 0.812 inches and 0.817 inches	
	nternal Drive Style:	
	offset cruciform (torque set)	
	hread Diameter:	
	190 inches	
	hready Qty Per Inch (tpi):	
3		
	lin. Tensile Strength (psi):	
	60000 pounds per square inch	
	xternally Relieved Body Diameter Quantity:	
1		
	roduct Name:	
	avy special project	
	laterial:	
	on alloy 660	
	laterial Specification:	
	ms 5737 assn standard single material response	
	urface Treatment:	
	assivate	
	urface Treatment Specification:	
C	q-p-35 federal specification single treatment response	
т	hread Series Designator:	
U	njf	
S	helf Life:	
N	/a	

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0