NSN 5305-01-022-1290



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-022-1290 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.641 inches and 0.671 inches **Fastener Length:** Between 1.370 inches and 1.380 inches **Head Style:** Flat chamfer **Head Diameter:** 0.880 inches **Head Height:** 0.125 inches **Shoulder Diameter:** 0.680 inches first shoulder and 0.683 inches first shoulder **Shoulder Length:** 0.469 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.139 inches all holes and 0.145 inches all holes **Internal Drive Style:** Slot **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 13 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.203 inches first hole **Shoulder Shape:** Round first shoulder Material: Stainless steel **Material Specification:** Aisi 316 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-022-1290

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0