NSN 5305-01-022-3061

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-022-3061

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| 0.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.303 inches and 0.312 inches |
| Head Height: |
| Between 0.185 inches and 0.190 inches |
| Locking Feature: |
| Patch threads or pellet threads or strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.190 inches |
| Width Across Flats: |
| Between 0.156 inches and 0.158 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 39.5 rockwell c |
| Chamfer Angle: |
| 45.0 degrees |
| Material: |
| Steel fastener |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium fastener and chromate fastener |
| Surface Treatment Specification: |
| Qq-p-416, type 2 class 2 federal specification single treatment response fastener |
| Thread Series Designator: |
| Unjf |
| Specification Data: |

80205-nas1351 professional/industrial association standard

NSN 5305-01-022-3061

Socket Head Cap Screw - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0