## NSN 5305-01-023-1924

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-023-1924 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.396 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.167 inches and 0.171 inches **Head Height:** 0.150 inches **First Diameter From Head:** Between 0.076 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.146 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Chamfered head Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

## NSN 5305-01-023-1924

Externally Relieved Body Screw - Page 2 of 2



| H | nit | Ωf  | M    | eas | ur | Δ. |
|---|-----|-----|------|-----|----|----|
| v |     | . 0 | 1414 | -u3 | uı | С. |

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.