

View Online at <https://aerobasegroup.com/nsn/5305-01-023-1926>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.340 inches and 1.500 inches

**Fastener Length:**

Between 1.440 inches and 1.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.735 inches and 0.750 inches

**Head Height:**

Between 0.492 inches and 0.500 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.500 inches

**Width Across Flats:**

Between 0.375 inches and 0.379 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

150000 pounds per square inch

**Material:**

Steel fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416, type 2 class 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0