

View Online at <https://aerobasegroup.com/nsn/5305-01-023-2422>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

2.000 inches

**Fastener Length:**

Between 2.670 inches and 2.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.107 inches and 1.125 inches

**Head Height:**

Between 0.740 inches and 0.750 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.750 inches

**Width Across Flats:**

Between 0.625 inches and 0.631 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

150000 pounds per square inch

**Material:**

Steel

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl 1 military specification single treatment response

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.