## NSN 5305-01-023-5844

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-023-5844 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.710 inches and 0.760 inches **Fastener Length:** Between 1.095 inches and 1.125 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.951 inches and 1.014 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Titanium alloy uns r54520 **Material Specification:** Nas621, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas668 professional/industrial association standard Shelf Life: N/a

...

**Unit Of Measure:** 

## NSN 5305-01-023-5844

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0