Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-023-6238

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.218 inches
Fastener Length:
Between 0.280 inches and 0.312 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.253 inches
Secondary Washer Outside Diameter:
Between 0.253 inches and 0.263 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.031 inches
Secondary Washer Material Thickness:
Between 0.013 inches and 0.019 inches
Material:
Steel comp 430 or steel comp 302 or steel comp 303 or steel comp 301 or steel comp 304 or steel comp 316 or stainless steel
Surface Treatment:
Passivate
Thread Series Designator:

Unc

## NSN 5305-01-023-6238

Assembled Washer Screw - Page 2 of 2



**Specification Data:** 

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0