NSN 5305-01-024-4734



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-024-4734 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.035 inches and 0.188 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** Fed-std66 federal standard all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:**

Mil-c-13924, cl 4 military specification single treatment of Thread Series Designator:
Unc
Specification Or Standard:
3 type and 3c style
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-024-4734

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.