## NSN 5305-01-024-7076

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-024-7076 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.782 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Material: Steel fastener **Material Specification:** 66 federal standard single material response fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification 1st treatment response fastener or mil-c-81562, type 2, cl 3 military specification 2nd treatment response fastener **Thread Series Designator: Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-01-024-7076

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.