NSN 5305-01-025-4789

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-025-4789 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.303 inches and 0.313 inches **Fastener Length:** 1.750 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** Between 0.546 inches and 0.578 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.249 inches and 1.259 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-025-4789

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.