NSN 5305-01-025-6431

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-025-6431

Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.280 inches and 0.371 inches					
Fastener Length:					
Between 0.424 inches and 0.464 inches					
Head Style:					
Pan					
Head Diameter:					
Between 0.361 inches and 0.385 inches					
Head Height:					
Between 0.103 inches and 0.118 inches					
Shoulder Diameter:					
0.186 inches first shoulder and 0.189 inches first shoulder					
Shoulder Length:					
0.072 inches first shoulder and 0.082 inches first shoulder					
Internal Drive Style:					
Cross recess type 1					
Thread Diameter:					
0.138 inches					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
125000 pounds per square inch					
Hardness Rating:					
26.0 rockwell c and 32.0 rockwell c					
Shoulder Shape:					
Round first shoulder					
Material:					
Steel comp 8630 or steel comp 4037					
Surface Treatment:					
Cadmium and chromate					
Surface Treatment Specification:					
Qq-p-416 ty2 class 2 federal specification single treatment response					
Thread Series Designator:					
Unjc					
Specification Data:					
80205-nas1298 professional/industrial association standard					
Shelf Life:					

N/a

NSN 5305-01-025-6431

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0