## NSN 5305-01-026-0836

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-026-0836 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.886 inches and 1.916 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches **Hole Diameter:** 0.038 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches **Grip Length:** Between 1.615 inches and 1.635 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Hole Configuration Style:** Round Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

## NSN 5305-01-026-0836

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1121 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No