Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-026-4359

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.129 inches and 0.181 inches
Fastener Length:
Between 0.359 inches and 0.391 inches
Head Style:
Fillister
Head Diameter:
Between 0.124 inches and 0.140 inches
Head Height:
Between 0.053 inches and 0.062 inches
First Diameter From Head:
Between 0.056 inches and 0.066 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.210 inches and 0.230 inches
Internal Drive Style:
Slot
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Thread Series Designator:
Shelf Life:
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-026-4359

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072 spec.