NSN 5305-01-026-5098

Machine Screw - Page 1 of 2

A500d0



View Online at https://aerobasegroup.com/nsn/5305-01-026-5098
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.423 inches and 0.500 inches
Fastener Length:
Between 1.641 inches and 1.687 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.270 inches and 0.306 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
100.0 degrees
Product Name:
Navy special project
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

NSN 5305-01-026-5098

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.