NSN 5305-01-026-5098

Machine Screw - Page 1 of 2

A500d0



| View Online at https://aerobasegroup.com/nsn/5305-01-026-5098 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.423 inches and 0.500 inches |
| Fastener Length: |
| Between 1.641 inches and 1.687 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.270 inches and 0.306 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Product Name: |
| Navy special project |
| Screw Material: |
| Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 |
| Screw Material Specification: |
| Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military |
| specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material |
| response |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

NSN 5305-01-026-5098

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.