

View Online at <https://aerobasegroup.com/nsn/5305-01-026-5105>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.268 inches and 0.315 inches

**Fastener Length:**

Between 1.572 inches and 1.612 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.449 inches and 0.507 inches

**Locking Feature:**

Detent ball grip

**Grip Diameter:**

Between 0.2483 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.125 inches and 1.145 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

100.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.464 inches first hole and 1.484 inches first hole

**Material:**

Steel comp 8740

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Fs251 fscm 76301 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0