NSN 5305-01-027-2003

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-027-2003 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.386 inches and 0.416 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.138 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-027-2003

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0