NSN 5305-01-027-4659

Close Tolerance Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-027-4659

| Thread Class: |
|---|
| |
| 3a Thread Direction: |
| |
| Right-hand |
| Thread Length: Between 0.443 inches and 0.510 inches |
| |
| Fastener Length: Between 0.828 inches and 0.875 inches |
| |
| Head Style: Flat countersunk undercut |
| |
| Head Diameter: |
| Between 0.502 inches and 0.507 inches |
| Head Height: |
| Between 0.071 inches and 0.073 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| High-torque Thread Diameter: |
| |
| 0.250 inches |
| Grip Length: |
| Between 0.365 inches and 0.385 inches |
| Thready Qty Per Inch (tpi): 28 |
| |
| Countersink Angle: 100.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-027-4659

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

