## NSN 5305-01-027-4664

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-027-4664 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.573 inches **Fastener Length:** Between 1.078 inches and 1.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.629 inches and 0.634 inches **Head Height:** Between 0.088 inches and 0.090 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Furnished with one o-ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

## NSN 5305-01-027-4664

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0