NSN 5305-01-027-5233

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-027-5233 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 2.250 inches **Fastener Length:** Between 4.360 inches and 4.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.479 inches and 1.500 inches **Head Height:** Between 0.988 inches and 1.000 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 1.000 inches Width Across Flats: Between 0.750 inches and 0.757 inches Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch **Product Name:** Navy special project Material: Steel fastener **Surface Treatment:** Oxide fastener **Surface Treatment Specification:** Mil-c-13924, class 3 military specification single treatment response fastener **Thread Series Designator:**

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

NSN 5305-01-027-5233

Socket Head Cap Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
F::	
Fiig:	

Shelf Life:

Mil-std (military Standard):

Mil-c-13924 spec.