NSN 5305-01-027-6402

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-027-6402

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.278 inches and 0.329 inches
Fastener Length:
Between 3.731 inches and 3.751 inches
Head Style:
Pan
Head Diameter:
Between 0.477 inches and 0.492 inches
Head Height:
Between 0.126 inches and 0.141 inches
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Grip Length:
Between 3.312 inches and 3.328 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
63.0 microinches grip
Special Features:
Retaining balls in shank 180 degrees apart
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5305-01-027-6402

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0