

View Online at <https://aerobasegroup.com/nsn/5305-01-028-2442>

**Fastener Length:**

0.500 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.195 inches and 0.225 inches

**Internal Drive Style:**

Slot

**Min. Tensile Strength (psi):**

50000 pounds per square inch

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Countersink Angle:**

81.0 degrees

**Nonmachine Thread Diameter:**

0.112 inches

**Material:**

Copper alloy 260 or copper alloy 268 or copper alloy 270

**Material Specification:**

Qq-b-613 1/4 hard federal specification 1st material response or qq-b-626 1/4 hard federal specification 1st material response or qq-w-321 1/4 hard federal specification 1st material response or qq-b-613 1/4 hard federal specification 2nd material response or qq-b-626 1/4 hard federal specification 2nd material response or qq-w-321 1/4 hard federal specification 3rd material response

**Surface Treatment:**

Chromium

**Specification Or Standard:**

1 type and 2s style

**Departure From Cited Document:**

As modified by surface treatment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0