NSN 5305-01-028-3292

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-028-3292 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.764 inches and 0.875 inches **Fastener Length:** 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch **Surface Finish:** 63.0 microinches grip Material: Steel **Surface Treatment:** Zinc **Surface Treatment Specification:** Astm b633 assn standard single treatment response **Thread Series Designator:**

Unc

Shelf Life:

N/a

NSN 5305-01-028-3292

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0