

View Online at <https://aerobasegroup.com/nsn/5305-01-028-3293>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.139 inches and 1.250 inches

**Fastener Length:**

1.250 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.457 inches and 0.469 inches

**Head Height:**

Between 0.306 inches and 0.312 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

0.250 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

150000 pounds per square inch

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel fastener

**Material Specification:**

Mil-f-18240 military specification single material response locking feature

**Surface Treatment:**

Zinc fastener and chromate fastener

**Surface Treatment Specification:**

Astm b633, type 2, class 3 assn standard all treatment responses fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-18240 spec.