Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-028-3293



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.139 inches and 1.250 inches Fastener Length: 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches Locking Feature: Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Surface Finish: 63.0 microinches grip Material: Steel fastener **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Zinc fastener and chromate fastener **Surface Treatment Specification:** Astm b633, type 2, class 3 assn standard all treatment responses fastener

## **Thread Series Designator:**

Unc

## NSN 5305-01-028-3293

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

## Mil-std (military Standard):

Mil-f-18240 spec.

