Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-028-3294

| view Online at https://aerobasegroup.com/nsn/3303-01-020-3234 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.389 inches |
| Fastener Length: |
| 1.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.457 inches and 0.469 inches |
| Head Height: |
| Between 0.306 inches and 0.312 inches |
| Locking Feature: |
| Patch threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c fastener and 45.0 rockwell c fastener |
| Minimum Yield Strength: |
| 155000 pounds per square inch |
| Material: |
| Steel uns k03104 fastener |
| Material Specification: |
| Mil-f-18240 military specification single material response locking feature |
| Surface Treatment: |
| Zinc fastener and chromate fastener |
| Surface Treatment Specification: |
| Astm b633 type 2 assn standard single treatment response fastener |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |

NSN 5305-01-028-3294

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.