NSN 5305-01-028-6463

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5305-01-028-6463

View Online at https://aerobasegroup.com/nsn/5305-01-028-6463
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Fastener Length:
Between 1.710 inches and 1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel
Material Specification:
66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 6
federal standard 4th material response or 66 federal standard 5th material response or astm a493 type xm-7 assn standard 6th material
response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a

Unit Of Measure:

NSN 5305-01-028-6463

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0