

View Online at <https://aerobasegroup.com/nsn/5305-01-029-0713>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.157 inches and 0.250 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Watertight

Head Diameter:

Between 0.256 inches and 0.294 inches

Head Height:

Between 0.087 inches and 0.097 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Features Provided:

O ring

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

75000 pounds per square inch

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0