## NSN 5305-01-029-6928

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-029-6928

<b>T</b> I	<b>O</b> 1 <b>D D</b>
Thread	Class:

2a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.093 inches

#### Fastener Length:

0.234 inches

#### Head Style:

Flat chamfer

#### Head Diameter:

0.125 inches

#### Head Height:

0.060 inches

#### Shoulder Diameter:

0.154 inches first shoulder and 0.155 inches first shoulder

#### Shoulder Length:

0.125 inches first shoulder

## Internal Drive Style:

Slot

#### Thread Diameter:

0.112 inches

## Thready Qty Per Inch (tpi):

40

#### Shoulder Shape:

Round first shoulder

#### Material:

Steel comp 303

#### **Material Specification:**

Astm a582 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Mil-f-14072, finish no. E300, type 2 military specification single treatment response

## Thread Series Designator:

Unc

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5305-01-029-6928

Shoulder Screw - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-f-14072 spec.

