NSN 5305-01-029-8870

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-029-8870 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.239 inches and 0.259 inches **Fastener Length:** 1.312 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** Between 0.224 inches and 0.276 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.928 inches and 0.948 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard 1st material response or a276-55 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-029-8870

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.